

## FOREST FX PUR

### Descrizione

Pavimento vinilico eterogeneo, antistatico, stratificato, stampato effetto legno, pressato flessibile, saldabile. Trattamento poliuretano rinforzato di superficie.

### Traffico

Commerciale molto pesante.








### Composizione

Resine viniliche, plastificanti, stabilizzanti, pigmenti coloranti, cariche inerti, fibra di vetro, poliuretano. Strato intermedio: film vinilico stampato. Supporto: film vinilico stabilizzato in fibra di vetro.

Caratteristiche generali	Descrizione
Spessore	ISO 24346 EN 428 2,0 mm
Strato d'usura	ISO 24340 (EN 429) 0.70mm
Peso	ISO 23997 (EN 430) 2,66 kg/mq
Dimensioni, colori e confezioni	2 m x 20 m <b>18 colori</b> (mq 30)
Performance generali	ISO 10582 EN 649: Conforme ASTM F1303 Conforms Type I, Grade I, Class B Backing
Classe d'uso	ISO 10874 EN 685 <b>34,43</b>
Resistenza all'usura	EN 13893: Class DS; DIN 51130 / DIN EN 16165 Ann. B: <b>R10</b> AS 4586 Appendix D: <b>R10</b> ASTM D2047: SCOF $\geq 0.5$
Contenuto legante	ISO 10582 Tipo I
Resistenza all'abrasione	EN 649 Gruppo T
Reazione al fuoco	EN 13501-1 Bfl-s1
Comportamento elettrico	EN 1815 $\leq 2kV$ Antistatico
Resistenza all'impronta	ASTM F1914 $\leq 0.005''$ ASTM F970 (modificato) $\leq 0.005''$ (750 psi); ISO 24343-1 $\leq 0.10mm$
Sedia a rotelle	ISO 4918 EN 425: idoneo





Stabilità dimensionale	ISO 24344 ENE 434 $\leq 0.40\%$
Flessibilità	ISO 24344 (EN 435) (Method A) Pass 20mm $\varnothing$ ASTM F137: 0,25"
Riscaldamento a pavimento	Idoneo, max 27° C
Solidità alla luce	ISO 105-B02 (Method 3) $\geq 6$
Resistenza alla luce	ASTM F1515 $\Delta E \leq 8.0$ - Meets
Resistenza al calore	ASTM F1514 $\Delta E \leq 8.0$ - Meets
Sostenibilità	Prodotto certificato Floorscore Indoor Air Comfort Gold: prodotto certificato Eurofins AgBB passato; Finnish M1 passato; REACH conforme
Emissioni VOC	TVOC dopo 28 giorni $\leq 10\mu\text{g}/\text{m}^3$
Certificazioni	      





**Parish Oak Parquet 3106**  
plank size in sheet: 76.2 x 288.6mm  
w/r 9841 LRV 32



**Blanched Oak 3113**  
plank size in sheet: 200 x 1000mm  
w/r 3113 LRV 42



**Oslo Oak 3104**  
plank size in sheet: 167 x 1500mm  
w/r 9829 LRV 32



**Newport Oak 3109**  
plank size in sheet: 167 x 1500mm  
w/r 9838 LRV 30



**Grey Sawmill Oak 3101**  
plank size in sheet: 180 x 1000mm  
w/r 3101 LRV 40



**Rock Salt Oak 3103**  
plank size in sheet: 220 x 1500mm  
w/r 3103 LRV 37



**Alloyed Timber 3105**  
plank size in sheet: 167 x 1500mm  
w/r 9841 LRV 24



**Oiled Oak 2990**  
plank size in sheet: 167 x 1500mm  
w/r 2990 LRV 35



**Rural Deckwood 3102**  
plank size in sheet: 180 x 1000mm  
w/r 3102 LRV 28



**Eton Oak Parquet 3108**  
plank size in sheet: 76.2 x 288.6mm  
w/r 9822 LRV 24



**Classic Oak 3100**  
plank size in sheet: 167 x 1500mm  
w/r 3330 LRV 29



**Rustic Oak 3330**  
plank size in sheet: 84 x 332/664mm  
w/r 3330 LRV 29



**American Oak 3380**  
plank size in sheet: 100 x 1000mm  
w/r 3380 LRV 36



**European Oak 3340**  
plank size in sheet: 100 x 1000mm  
w/r 3340 LRV 21



**French Walnut 3120**  
plank size in sheet: 167 x 1000mm  
w/r 3120 LRV 17



**Smoked Oak 3150**  
plank size in sheet: 167 x 1500mm  
w/r 3150 LRV 14



**Mahogany 3360**  
plank size in sheet: 84 x 332/664mm  
w/r 3360 LRV 10



**Brazilian Walnut 3990**  
plank size in sheet: 133 x 1000mm  
w/r 3990 LRV 8